



HHT894 **HD** TV Receiver

HHT894 High Definition Digital TV receiver features all AV outputs active simultaneously. Easy to install it is built in a small footprint case less than 220mm wide with a removable mains power lead. Full 7 day Electronic Program Guides, Closed Caption subtitles and Teletext are included in the

HHT894 whilst Optical Digital Audio can provide full Surround Sound. Equipped with a proven SGS Thomson main chip, healing HHT894 delivers beautiful High Definition and Standard Definition Television pictures.



**receives all
free to view
channels**



Features Include:

- Resolutions: 1920 x 1080i, 1280 x 720p, 720 x 576p and 720 x 576i
- HDMI, Component Y/Pb/Pr and Composite CVBS Video outputs
- 7 day Electronic Program Guide (EPG) with 8th day cross over
- Full Closed Caption and Teletext functions embedded
- Automatically updates broadcaster program changes
- Centre Cut option displays 16/9 on 4/3 screens
- Signal Strength and Quality bars colour coded
- Stores up to 360 TV and Radio channels
- Saves program parameters at Power Fail
- All Video outputs active simultaneously
- Compact case less than 220mm wide
- Optical Digital Audio SP/DIF output
- Outstanding HD picture quality
- Our most sensitive tuner yet





HHT894 **HD** TV Receiver



Specifications

Decodes	High Definition and Standard Definition Digital Terrestrial TV & radio.	Software upgrade	via RS-232 serial port
Video Outputs	HDMI, Component Y Pb Pr and Composite CVBS.	IR receiver	38KHz
Video Resolutions	1920x1080i, 1280x720p, 720x576p or 720x576i.	Mains Power	AC90 - 250Volts @ 50/60Hz
Aspect Ratios	Widescreen 16:9, Centre Cut 4:3 or Letterbox 4:3.	Power Consumption	rated at 15W , typical 12W, .6W standby Energy Safe Victoria MEPS registered.
Audio Outputs	CD quality Analogue via RCA's or Digital Optical AC3 via Toslink. with AC3 (5.1), where broadcast.	Operating Temperature	0 - 40°C
Audio modes	Stereo, Dual Channel, or Mono.	Case Dimensions	218mm Wide x 44mm High x 170mm Deep
Teletext	via integrated software decoder, where broadcast.	Weight	<1Kg
Closed Captions	via Teletext decoder (page 801).	Accessories Included	1 x Remote Control Unit 2 x AAA Batteries 1 x 3 RCA - 3 RCA AV lead 1.5m 1 x IEC C7 figure 8 mains lead 1 x Owners Manual
EPG Information	7 day SI EIT p/f tables (including cross-over).		
Memory	4MB Flash RAM; 64MB Double Data Rate RAM.		
Main Chip			
Tuner sensitivity	typical -80.6 dBm to -82.5 dBm.		
Frequency range	VHF & UHF 175 - 820MHz.		
Channel bandwidth	7MHz.		
Modulation mode	COFDM 8K or 2K, automatic detection.		
Constellation	QPSK, 16QAM or 64QAM.		
Guard interval	1/4, 1/8, 1/16 or 1/32		



Low Power Consumption
Government MEPS registered